

SAFETY DIRECTIVE

Check of Air box for all Eurofox to S/N 15804

Symbols:

Please pay attention to the following symbols throughout this document emphasizing particular information.

▲ WARNING: Identifies an instruction, which if not followed, may cause

serious injury or even death.

CAUTION: Denotes an instruction which if not followed, may severely

damage the aircraft or could lead to suspension of warranty.

◆ **NOTE**: Information for better handling.

1. General information

<u>Issued by:</u> Aeropro, s.r.o. Nitra, Dlhá 126, Slovakia <u>www.aeropro.sk</u>

Release date: Fuebfuary-02-2005, initial issue

<u>Date of effect:</u> Immediately

Limit to accomplish

the task: Prior to next takeoff

<u>Issue number:</u> SD Aeropro EF 01/2005

1.1 Planning information

Models affected: All Eurofox form S/N.: 075099 to 15804

S/N affected: from 075099 to 15804 include it

Reason: Aeroplanes of this S/N had been installed aluminium air box. Creak

had detected on this welding edges of bottom air box.


Subject: Check surface and edges of the air box

2. Material information

<u>Tools needed:</u> 7/8/10 mm open ended spanners, pliers, screwdriver

<u>Parts needed:</u> Composite Air box (delivery by Aeropro), air filter

Date: 2.2.2005



$oldsymbol{A} oldsymbol{E} oldsymbol{R} oldsymbol{O} oldsymbol{P} oldsymbol{R} oldsymbol{O}$, Producer LSA Aeroplanes

Dlhá 126, Nitra Slovakia

www.aeropro.sk

3. Accomplishment

<u>Level of maintenance:</u> Heavy

3.2

<u>Certification required:</u> A&P Mechanic or LSA Repairman maintenance

▲ WARNING: Proceed this work only in a non-smoking area. Switch off ignition

and secure engine against unintentional operation.

<u>Instructions:</u> Mechanic has to continue according this basic points:

Open air box and check if air box is without crack on it welding edges. If the air box is without crack then you close it.

If you have find some cracks on the air box then you have to

change it for new composite air box.

3.3 Remove read elastic tube /picture 1-1 p.1/

Remove upper part of air box /picture 1-1 p.2/

3.5 Take away air filter

3.6 Uninstall every four rings which holding rubber elbows between

carburettors and air box

3.7 Remove bottom parts of air box

3.8 For installation new composite air box continue backtrack of

this points.

◆ NOTE: The new composite air box /picture 1-1 p 4 / has had same

dimension as old aluminium air box.

<u>Test / Inspect:</u> After installation check every parts in the engines area. Test of

installation was made during worming of engine and engine test on

the ground

Summary:

▲ WARNING: Non-compliance with these instructions could result in personal

injury or death.

Date: 2.2.2005 2/3



Picture 1-1





Date: 2.2.2005 3/3